

## Dual-window multimode fiber



### Overview

As one of the key components for GPON FTTx networks, optical splitters can be placed in the Central Office or in one of the distribution points (outdoor or indoor) because the FBT splitters are highly stable for multipoint optical signal splitting. As one of the key components for GPON FTTx networks, optical splitters can be placed in the Central Office or in one of the distribution points (outdoor or indoor) because the FBT splitters are highly stable for multipoint optical signal splitting with low insertion loss. FBT couplers are designed for power splitting and tapping in telecommunication. For FBT Splitters, Fiber-Mart provides a whole series of this kind customized for specific applications: a. Different coupling ratio can be customized according to your requirement. b. Two out of the 1310nm, 1490nm and 1550nm operating wavelength can be selected. c. 1x2, 1x3, 1x4, 1x5, 1x6, 1x8, 1x12, 1x16, 1x18, 1x20, 1x24, 2x2, 2x4, 3x3 configurations. Fiber-Mart offers cost-effective standards-based 1x8 Multimode Dual Window 250um Bare Fiber Splitter FBT Splitter. As a 3rd party OEM manufacturer, our 1x8 Multimode Dual Window 900um Loose Tube Fiber Splitter is delivered worldwide from our factory directly, and they are all based on thin film filter technology and metal bonding micro optics pa.

## Dual-window multimode fiber



Fiberdyne Labs Dual Window Couplers/Splitters devices are bi-directional. They can be used to combine a signal (Couplers) or divide a signal (Splitters).



Single mode & multimode couplers available online from Fibertronics with same day shipping. The available split counts are 1x2 and 2x2 or 1x4 1X8.



The Multimode Dual Window Coupler from Sunny Precision Optics is a Fiber Optic Coupler with Excess Loss 1 dB, Insertion Loss 4.4 dB, Bandwidth  $\pm 40$  nm, Wavelength 850 nm, 1310 nm, Directivity  $> 40$  dB.



The multi-mode wideband fiber couplers manufactured by Hiphotonics are frequently utilized in data link systems. In these systems, they assist in the process of connecting several devices to a single network.



The MPS-2350 Multimode Optical Splitter/Coupler is available in a variety of configurations and split ratios to meet your specifications. The MPS-2350 can be ordered with any of the following operating ...



Thorlabs offers 1x2 graded-index (GRIN) multimode, dual-window fiber couplers with  $\text{\O}50$   $\mu\text{m}$  core graded-index fibers. These couplers operate at both 850 nm and 1310 nm wavelengths.



Window Fiber Splitter with ABS Box is delivered to worldwide from our factory directly, and they are all based on thin film filter technology and metal bonding micro optics packaging.



Fiberdyne Labs Dual Window Couplers/Splitters devices are bi-directional. They can be used to combine a signal (Couplers) or divide a signal (Splitters).



Overall, double-window fiber is an excellent choice for applications that require the transmission of two different signals over a single fiber cable. It is reliable, lightweight, and flexible, and can be used with ...



As a 3rd party OEM manufacturer, our 1x8 Multimode Dual Window 900um Loose Tube Fiber Splitter is delivered to worldwide from our factory directly, and they are all based on thin film ...

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://indzawo.co.za>

Email: [sales@indzawo.co.za](mailto:sales@indzawo.co.za)

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

