

# How to configure a dual-line aggregation switch



## Overview

In this article, I'm going to describe how to set up Link Aggregation between two managed switches to provide connectivity, redundancy, and expanded bandwidth. LACP (Link Aggregation Control Protocol): LACP is an industry-standard protocol (802.3ad) that dynamically manages link aggregation, provides automatic failover, and helps prevent misconfigurations by ensuring both ends of the link agree on the aggregation settings. Step 1: Start by connecting two switches together by multiple ports which you would like. This article shows how Link Aggregation Groups (LAGs) are implemented on Dell Networking Switches. Options for LAG Port Channel Type 2. Here's how it works step-by-step: Port Bundling: Two or more Ethernet ports are "bundled" into a single logical port. Load Sharing: Traffic is split between the bundled ports using load-balancing algorithms. · VLAN 20 on Device A can communicate with VLAN 20 on Device B. For example, two 10-gigabit Ethernet ports, one each from two MLAG configured switches, can connect to two 10-gigabit ports on a host, switch, or network device to create a link that.

## How to configure a dual-line aggregation switch



Deploying MLAG removes over-subscription by configuring an MLAG link between two aggregation switches to create a single logical switching instance that utilizes all connections to the switches.



Link Aggregation provides the ability to group multiple Ethernet interfaces to form a trunk which looks and acts like a single physical interface. This feature is useful for high end deployments ...




Instructions This article shows how Link Aggregation Groups (LAGs) are implemented on Dell Networking Switches.



Link Aggregation Control Protocol (LACP) is a standards-based method to control the bundling of several physical network links together to form a logical channel for increased bandwidth and ...




To learn how to configure an MC-LAG setup, see this guide. Find help and support for Ubiquiti products, view online documentation and get the latest downloads.



You can configure LAGs to connect a QFX Series product or an EX4600 switch to other switches, like aggregation switches, servers, or routers. This example describes how to configure LAGs to connect ...



- Set up a two-chassis IRF fabric at the access layer and a two-chassis IRF fabric at the distribution layer of the enterprise network.
- Configure link aggregation to improve the reliability of the links between ...



This guide covers link aggregation—what it is, why you need it, how to set it up, and key troubleshooting tips.



Learn how to configure dual Ethernet cards to increase network throughput on Linux.



I'm going to set up Link Aggregation between two gigabit switches: an 8 port Linksys SRW2008; and a 16 port Netgear GS716GT, shown in Figures 1 and 2 below. We covered both switches here a while ...

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://indzawo.co.za>

Email: [sales@indzawo.co.za](mailto:sales@indzawo.co.za)

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

