






Ex d-level explosion-proof distribution box and terminal block



Overview

A series of terminal and junction boxes made from aluminum. Ex d and Ex tb certified for installation in explosion-hazardous areas. Suitable for use in gas group IIB+H 2 environments. Customizable configuration of operators, cable entry quantities and cable gland types as per. Flameproof enclosure (Ex d IIB+H2), which can be used as feed distribution equipment in control and distribution system (such as distribution box, switch box of main circuit, control box, terminal box or motor starting box etc.) ·Enclosure: stainless steel. These sturdy solutions are certified according to global standards such as ATEX, IECEx. The main switch and branch switch are operated with the external rotary actuator. Rated voltage:250/400V;50/60Hz.

Iciib-level explosion-proof distribution box and terminal block


 <p>INSTALLATION METHOD</p>	<p>Designed to withstand extreme temperatures, EJBX terminal boxes and junction boxes support operation in environments as cold as -60 °C. Customers can have each unit tailored to their ...</p>
	<p>Power Distribution panel box - Hazardous locations for explosive gas mixtures: Zone 1 and Zone 2. Explosive gas mixtures: Class IIA, IIB, and IIC.</p>
	<p>Internal wiring to the terminal is finished. The international brand of terminal blocks and components. Copper-free Aluminum Alloy (carbon steel), powder-coated surface, or stainless steel. Special ...</p>
	<p>The enclosures are certified Ex d IIB+H2 and Ex tb as well as "explosion-proof". They are available in many sizes, a wide range of operating elements and monitoring functions can be integrated. They ...</p>
	<p>International brand of terminal blocks and components. Copper-free Aluminium Alloy (carbon steel), powder coated surface, or stainless steel. Special requirements on request.</p>



An IIB+H2 Explosion-Proof Terminal Box is a specific type of explosion-proof enclosure designed to be used in environments where hazardous gases, vapors, and other explosive atmospheres are present.



Need help choosing the right product? Contact our experts or request a quote today. Degree of protection:IP66. Rated voltage:250/400V;50/60Hz.



Huijue engineering specific Fiber optic
HJ GROUP offers a wide variety of product types for you to choose from.


Equipped with specialized hinge structure, which can prevent the flameproof joints from damage when opening and closing the panels, and greatly prolong the service life of box. The boxes can be ...



Internal wiring to the terminal is finished. The international brand of ...



Internal wiring to the terminal is complete. International brand of terminal used. Copper-free aluminium (carbon steel), powder coated surface, or stainless steel. Entries plugged. Cable glands on request ...



International brand of terminal blocks and components. Copper-free Aluminium Alloy (carbon steel), powder coated surface, or stainless steel. Special requirements on ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://indzawo.co.za>

Email: sales@indzawo.co.za

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

