


Outer diameter of 24-core outdoor single-mode optical cable




Outer diameter of 24-core outdoor single-mode optical cable



Material: PE Color: Black Outer Diameter: 6.5mm.
All jackets and colors for Riser, Plenum,
Indoor/Outdoor, LSZH, Burial & Industrial projects.



It is composed of 24 singlemode fibers (9 micron core) inside a water blocking Aramid yarn wrapped in a black PVC outer jacket. Single mode fiber is optimized to work with fiber optic equipment using light ...



This cable design is available in both riser rated and plenum rated versions for deployment in any inside plant re-code application. The UV-resistant outer jacket, coupled with dry waterblocking technology, ...



The all-dielectric cable construction requires no bonding or grounding, and these cables have a medium-density polyethylene jacket that is rugged, durable and easy to strip.




up to 4 - 24 optical fibers in water blocked loose tube. Taped, corrugated steel tape armored (STA); polyethylene (HDPE) outer sheath; and embedded with two steel wires on the periphery. T



This cable is suitable for underground installation, overhead lashed to a guy wire, or secured to a building or other permanent outdoor structure. The drawback of the gel-filled cable is that it is ...



Discover the TiniFiber TF24-OS2-PLO, a single-mode fiber optic cable designed for both indoor and outdoor use. It boasts the smallest and lightest armored design, making installation quick and hassle ...



This cable has flame retardant and LSZH properties and is ideal for indoor installations. The cable is water-blocked and well suited for installation in ducts and on trays indoors and limited outdoor use in ...



Micro Armor Fiber™ The Original Stainless Steel Armor Single Mode 24 Fiber 250mm OS2 Armored OSP/Outdoor Polyethylene Fiber Optic Cable Model #TF24-OS2-PE en installed according to NEC® ...



Our comprehensive chart simplifies the process by outlining the key dimensions—core size, cladding size, coating diameter, and buffer size—that technicians, engineers, and buyers need ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://indzawo.co.za>

Email: sales@indzawo.co.za

Phone: +27 71 296 8473

Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

