Vietnam-branded carrier-grade router QSFP-DD

Overview

QSFP-DD is a new module and cage/connector system similar to current QSFP, but with an additional row of contacts providing for an eight lane electrical interface. It is being developed by the QSFP-DD MSA as a key part of the industry's effort to enable high-speed. The Cisco ® family of QSFP-DD modules provide the industry's highest bandwidth density while leveraging the backward compatibility to lower-speed QSFP pluggable modules and cables. The Cisco 400GBASE Quad Small Form-Factor Pluggable Double Density (QSFP-DD) portfolio offers customers a wide variety. Quad Small Form-factor Pluggable Double Density (QSFP-DD) solution that fits into high-density switch and router client ports for optical interconnect links Powered by Greylock and Delphi DSP ASICs, and silicon photonic integrated circuits (PICs) for an optimized co-packaged design with 3D. The core difference between SFP and QSFP is lane count: SFP is a single-lane form factor (1G–25G), while QSFP aggregates 4 (or more) lanes to reach 40G, 100G, 200G and 400G (QSFP-DD). Choose by port density, target bandwidth, distance, and thermal budget. QSFP-DD connector portfolio's backwards compatibility allows. Supporting the continuing growth in the bandwidth demand and datacenter traffic driven by

networking and AI/ML requirements, the QSFP-DD (Double Density) Interconnect System delivers 8 lanes with up to 28 Gbps NRZ or 56 Gbps-PAM4 (up to 400 Gbps aggregate) in a compact footprint that is backward. InnoLight 100G OpenZR+ QSFP-DD product family is designed based on dual polarization quadrature phase shift keying (DP-QPSK), supporting extended C-band, polarization diversity coherent detection and advanced electronic link equalization.

Vietnam-branded carrier-grade router QSFP-DD

	QSFP-DD is a new module and cage/connector system similar to current QSFP, but with an additional row of contacts providing for an eight lane electrical interface. It is being developed by the QSFP-DD ...
	The core difference between SFP and QSFP is lane count: SFP is a single-lane form factor (1G–25G), while QSFP aggregates 4 (or more) lanes to reach 40G, 100G, 200G and 400G (QSFP-DD). Choose ...
	It provides a QSFP-DD-to-QSFP-DD copper direct-attach solution. QDD-400-CuxM cables are suitable for very short links and offer a cost-effective way to establish a 400-Gigabit link between ...
	QSFP-DD provides high-performance computing capability. The QSFP interconnects density is doubled with electrical interface, providing superior thermal and signal integrity.
	July 11, 2019 – QSFP-DD Hardware Specification for QSFP DOUBLE DENSITY 8X PLUGGABLE TRANSCEIVER – Rev 5.0 May 8, 2019 – Common Management Interface Specification – Rev 4.0

	QSFP-DD Interconnect System enables faceplate density equal to the current 2x1 QSFP form factor, but with 8-lane ports. In other words, a total of 256 differential pairs with 32 ports delivers double-lane ...
	Quad Small Form-factor Pluggable Double Density (QSFP-DD) solution that fits into high-density switch and router client ports for optical interconnect links
	The product supports 400Gbps transmission speeds in an industry-standard, pluggable QSFP-DD form factor with 7nm DSP and can be widely used in metro carrier, access and Cloud/DCI applications.
	The high performance and low power of the 400G QSFP-DD ULH module make it an optimal choice to extend Routed Optical Networking use cases to regional and ultra-long-haul ...
	Quad small form pluggable double density (QSFP-DD) transceivers maximize port economy and density by utilizing multiple lanes of data. QSFP-DD fiber transceivers utilize eight lanes as opposed to the ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: https://indzawo.co.za
Email: sales@indzawo.co.za
Phone: +27 71 296 8473
Address: 22 Quantum Street, Midrand, 1685, Gauteng, South Africa

This document is for informational purposes only. Specifications subject to change without notice.